



PLC-WXL46

- Ultra-short Focus Projector for short-distance-projections
- Brightness: 2.000 ANSI lumens, contrast ratio: 500 : 1
- WXGA Resolution (1.280 x 800 pixels) in 16 : 10 format
- Black-board mode for optimised projections onto coloured surfaces (e.g. interactive whiteboards)
- Direct Power On/Off allows switching the projector on/off without delay
- Anti-theft function through PIN code lock, Key lock
- MyLogo Function for custom logo transfer
- 3 years warranty, 1 year lamp warranty (max. 2,000 hours)

PLC-WXL46

TECHNICAL DATA	PLC-WXL46
EAN Code	4994334268853
Category	Business & Education
Panel	3 x 0.59" TFT p-Si (16:10), micro lens
Panel type	Organic LCD panel
Lamp	200 W UHP (LMP-106)
Brightness	2000 ANSI lumens
Brightness (eco mode)	1460 ANSI lumens
Lamp life	3000 h (eco mode) / 1500 h (normal mode)
Fan noise	31 dB (eco mode) / 38 dB (normal mode)
Standard lens	F = 1.80 / f = 6.60 mm *
Throw distance ratio	0.5 : 1
Throw distance	0.53 - 1.20 m
Contrast ratio	500 : 1
Resolution in pixels	1,280 x 800 (WXGA)
Image size min. - max. (diagonal):	50 - 110 inch
Uniformity	80 %
Bandwidth/Frequency	140 MHz, Horizontal frequency: 15 - 100 kHz, Vertical frequency: 50 - 100 Hz
Color systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: D-Sub15 (RGB/component) Input 2: D-Sub15 (RGB) or monitor out Input 3: RCA (composite) Input 4: Mini DIN 4 (S-Video) Audio: 3.5 mm stereo jack Audio: 2 x RCA (R/L mono) Audio output : 3.5 mm stereo jack Control input jack 1: Mini DIN 8 (RS232) Control input jack 2: RJ45 (LAN)
Audio function	1 W mono
Keystone correction	vertical +/- 20°
Up/Down ratio	10 : -1.7 (fixed U/D ratio)
HDTV compatibility	480i, 480p, 575i, 575p, 720p, 1,080i
Computer compatibility	UXGA, SXGA, SXGA+, WXGA, XGA, SVGA, VGA, Mac
Power consumption	190 W (eco mode) / 250 W (normal mode), 7.5 W (stand-by mode)
Voltage	100 - 240 V
Warranty	3 years, 24-hr replacement service (D/CH/I/F - except overseas), 1-year lamp warranty (max. 2,000 hours)
Dimensions (W x H x D)	319.9 x 148.4 x 300.9 mm
Weight (net)	3.4 kg
Standard accessories	IR remote control, Batteries, User manual, Power cable, D-Sub15 cable, PIN code label, Lens cover with cord, CD-ROM for network integration
Optional accessories	SCART/D-Sub15 cable (POA-CA-SCART), Components/D-Sub15 cable (POA-CA-COMPVGA), Ceiling mount 15 cm (POA-CM01), Ceiling mount 40-70 cm (POA-CM02), Ceiling mount 70-110 cm (POA-CM03)
Lenses	Standard lens

* You can use the distance calculator at www.sanyo.de to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 07/2009

