



PLC-XU111 | PLC-XU101

- Resolution native: 1,024 x 768 (XGA), maximum: 1,600 x 1,200 (UXGA)
- New lamp type with extended lifetime
- Brightness: 4,000 ANSI lumens; ultra portable
- Anti-theft function: audio alarm feature (PLC-XU111)
- Network integration with LAN connector (RJ45) and WLAN USB key (PLC-XU111)
- DVI-I input (PLC-XU111)
- MyLogo Function, Direct Power On/Off, Remote Control Code
- 360° projection possible
- 3 years warranty, 1 year lamp warranty

PLC-XU111 | PLC-XU101

TECHNICAL DATA	PLC-XU111	PLC-XU101
Category	Business & Education	
Panel	3 x 0.8" TFT p-Si (4 : 3), micro lens	
Projection Lamp	275 W NSH (LMP-111)	
Brightness in ANSI lumens	4,000	
Lamp Life	3,000 h (eco mode)/2,500 h (normal mode)	
Fan Noise	29 dB (eco mode)/32 dB (normal mode)	
Standard Lens	F = 1.7–2.1/f = 26.7–32 mm*	
Throw Distance Ratio	1.62–1.97 : 1*	
Throw Distance	1.3–10.0 m*	
Contrast Ratio	500 : 1	
Resolution in Pixels	1,024 x 768 (XGA)	
Image size min–max (diagonal)	33"–300"	
Uniformity	85 %	
Bandwidth/Frequency	140 MHz, horizontal 15~100 kHz, vertical 50~100 Hz	
Colour Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N	
Connections	Input 1: DVI-I (digital/HDCP/analog) Input 2: D-Sub15 (RGB/Component) Input 3: RCA (Composite) Input 4: Mini DIN 4-pin (S-Video) Input 5: USB type B for WLAN key Input 6: RJ45 (LAN) Audio: 2 x RCA (R/L mono) for Video, 3.5 mm Stereo Jack for Computer Monitor Output: D-Sub15 Audio Output: 3.5 mm Stereo Jack (variable) Control Input 1: Mini DIN 8-pin (RS232) Control Input 2: USB type B	Input 1: D-Sub15 Input 2: D-Sub15 (RGB/Component/SCART-RGB) Input 3: RCA (Composite) Input 4: Mini DIN 4-pin (S-Video) Audio: 2 x RCA (R/L mono) for Video, 3.5 mm Stereo Jack for Computer Monitor Output: D-Sub15 Audio Output: 3.5 mm Stereo Jack (variable) Control Input: Mini DIN 8-pin (RS232)
Audio Function	1 W Mono	
Keystone Correction	vertical +/-40	
Up/Down-Ratio	9 : 1 (Fixed U/D Ratio)	
HDTV Compatibility	720p/1,035i/1,080i (HDTV-compatible)	
Computer Compatibility	UXGA/WXGA/SXGA/XGA/SVGA/VGA	
Zoom/Focus	1.2 x/manual	
Power Consumption/Voltage	330 W (eco mode)/390 W (normal mode)/100–240 V	325 W (eco mode)/385 W (normal mode)/100–240 V
Warranty	3 years, 1 year lamp (max. 1,000 h)	
Dimensions (W x H x D)	334 x 78 x 232 mm	
Weight	3.5 kg	3.4 kg
Standard Accessories	User manual, power cable, IR remote control with laser pointer and mouse function, batteries, VGA cable, PIN code label, alarm function, carrying case, USB Wireless LAN adapter (POA-USB11G), CD-ROM for network integration	User manual, power cable, IR remote control, VGA cable, PIN code label
Optional Accessories	SCART-VGA cable (POA-CA-SCART), USB memory (POA-USB02), Component/D-Sub15 cable (POA-CA-COMPVGA), ceiling mounts: 15 cm (POA-CM01), 40–70 cm (POA-CM02), 70–110 cm (POA-CM03)	SCART-VGA cable (POA-CA-SCART), Component/D-Sub15 cable (POA-CA-COMPVGA), Remote control with laser pointer (POA-RCKIT03), presentation kit including mouse function (POA-RCKIT09), ceiling brackets: 15 cm (POA-CM01), 40–70 cm (POA-CM02), 70–110 cm (POA-
Lenses	CM03) Standard Lens	

* You can use the distance calculator at www.sanyo.de to determine exact image sizes and distances



Technical specifications subject to change without notice. Date 09/2007

