

Specifications

	DLA-HD550	DLA-HD950
Device	0.7inch D-ILA x3	
Resolution	1920 x 1080 pixels	
Lens	2x motorized zoom & focus f=21.4mm - 42.8mm F=3.2 - 4	
Lens shift	±80% Vertical / ±34% Horizontal (motorized)	
Projection size	60 - 200 inches	
Light source lamp	200W UHP (lamp life: approx. 3,000 hours in Normal mode)	
Brightness	1,000lm	900lm
Contrast ratio	Native: 30,000:1	Native: 50,000:1
Terminals	HDMI (ver.1.3) x2 Component x1 (RCA) S-Video x1 (mini DIN) Composite x1 (RCA) RS-232C (D-sub 9-pin)	HDMI (ver.1.3) x2 Component x1 (RCA) S-Video x1 (mini DIN) Composite x1 (RCA) PC x1 (D-Sub 15-pin) Trigger x1 (mini jack) RS-232C (D-sub 9-pin)
Video input signal	480i/p, 576i/p, 720p 60/50, 1080i 60/50, 1080p 60/50/24	
PC input signal	Digital	VGA/SVGA/XGA/WXGA/WXGA+/SXGA/WSXGA+/WUXGA
	Analog	- VGA/SVGA/XGA/WXGA/WXGA+/SXGA/SXGA+/WSXGA+
Noise level	19dB (Normal mode)	
Power requirement	AC 110V-240V, 50/60 Hz	
Power consumption	310W (Stand-by mode: 0.7W)	
Dimensions (W x H x D)	14.37" x 6.58" x 18.82" / 365 x 167 x 478 mm	
Weight	24.25 lbs. / 11.2kg	