



PDG-DWL2500



- Ultra-short Focus Projector with built-in 10 Watt speaker
- Throw ratio of 0.19 : 1 enables an 80" projection from a distance of merely 2.4 cm
- 3D-function for vivid visualisations without excessive space requirements
- Extremely low maintenance as a result of the integrated longlife-filters
- 6-segment color wheel
- WXGA resolution (1,280 x 800 pixels) in 16 : 10 format
- Brightness: 2,500 ANSI lumens (dynamic mode), contrast ratio: 2,000 : 1
- Network control via RJ45 (LAN)
- 3 years warranty, 1-years lamp warranty (max. 2,000 hours)

PDG-DWL2500

TECHNICAL DATA	PDG-DWL2500
EAN Code	4994334283337
Category	Business & Education
Panel	1 x 0.65 " DMD Chip (16:10)
Lamp	275 W NSH (LMP-143)
Brightness	2500 ANSI lumens, 2000 ANSI lumens (eco mode)
Lamp life	3000 h (eco mode) / 2000 h (normal mode)
Fan noise	28 dB (eco mode) / 36 dB (normal mode)
Standard lens	F = 2.5 / f = 4.83 mm *
Throw distance ratio	0.19 : 1
Throw distance	-0,066 - 0,159 m
Contrast ratio	2000 : 1
Resolution in pixels	1,280 x 800 (WXGA)
Image size min. - max. (diagonal)	60 - 110 inch
Uniformity	78 %
Bandwidth/Frequency	150 MHz, Horizontal frequency: 15 - 93 kHz, Vertical frequency: 50 - 120 Hz
Color systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Connections	Input 1: HDMI (HDCP) Input 2: D-Sub15 (RGB/component/S-Video) Input 3: D-Sub15 (RGB) or monitor out Input 4: RCA (composite) Input 5: Mini DIN 4 (S-Video) Audio: 2 x RCA (R/L mono) Audio: 2 x 3.5 mm stereo jack Audio output : 3.5 mm stereo jack Control input jack 1: D-Sub9 (RS232) Control input jack 2: RJ45 (LAN) Control input jack 3: Mini DIN 3 (3D function)
Audio function	10 W mono
Keystone correction	vertical +/- 5°
HDTV compatibility	480i, 480p, 575i, 575p, 720p, 1,080i, 1,080p
Computer compatibility	UXGA, SXGA, SXGA+, WXGA, XGA, SVGA, VGA, Mac, WUXGA
Zoom/Focus	-/manual
Power consumption / Voltage	305 W (eco mode) / 375 W (normal mode) / 0.8 W (stand-by mode) / 100 - 240 V
Unique features	Longlife-filter, 3D function, Eco mode, Power management, Automatic set-up (input search, keystone-correction, auto PC adjustment), Direct Power On/Off, Color-board mode, Color management function, MyLogo function, Freeze function, No Show mode, Picture reverse function, Picture inverse function, Key lock function, PIN code lock, Kensington lock, Presentation timer, Web management function, Email error reporting, SNMP log function, Multi language menu
Warranty	3 years, 24-hr replacement service (D/CH/I/F - except overseas), 1-year lamp warranty (max. 2,000 hours)
Dimensions (W x H x D)	321 x 178 x 386 mm
Weight (net)	6.2 kg
Standard accessories	IR remote control, Batteries, User manual, Power cable, D-Sub15 cable, PIN code label, Longlife-filter
Optional accessories	SCART/D-Sub15 cable (POA-CA-SCART) Wall mount (POA-CH-EX06)
Lenses	Standard lens

* You can use the distance calculator at www.sanyo.de to determine exact image sizes and distances

Technical specifications subject to change without notice. Date 09/2010

