

Samsung Digital Presenter

SDP-860



Specifications

		SDP-860
OPTICAL SYSTEM		
Lens		F=2.5 (Wide) ~ 3.2 (Tele) f=4.1 ~ 24.6mm, 6X Zoom Lens
Shooting Area		Max : 420 x 297mm
Zoom		48X Zoom (Optical 6X / Digital 8X)
Focus		Auto focus / Manual
Iris		Auto (with fine level adjustment)
VIDEO		
Pick-up Device		1/3" Progressive Scan CMOS Image Sensor
Total Number of Pixels		1,384(H) x 1,076(V), 1.49M pixels
Number of Effective Pixels		1329(H) x 1049(V), 1.39M pixels
Frame Rate		SXGA : 30fps
VGA Output		SXGA (1,280 x 1,024), XGA (1,024 x 768), HD (1,280 x 720p), 1,920 x 1,080p
Resolution		H : 700TV lines / V : 700TV lines
FUNCTIONS		
White Balance		AWC (One-touch) / ATW / Manual
Aperture Function		Image mode / Text mode / Custom mode
Noise Reduction		Available (Low light presenter with 2D/3D NR)
Preset Function		Up to 4 user settings
Image Freeze		Available
Image Rotation		Available (Flip / Mirror / 180 degree)
Image Save	Photo	JPEG, BMP
	Movie	MPEG-4 640 x 512@30fps with Audio (Mic) - Internal memory & SDHC card (up to 32GB)
Image Playback	Photo	Slide show / 3 x 3 (9-Split)
	Movie	Internal movie player
USB I/F		USB 2.0 support
Input Selection		2 Channels (Internal : 1, External : 1)
Illumination		LED Illumination system
INTERFACE		
Input Port	VGA In	15 pin DSUB Connector x 1
	Audio In	φ3.5 Jack x 1 (Built-in Microphone)
Output Port	VGA Out	15 pin DSUB Connector x 1
	DVI Out	DVI Connector
	Audio Out	φ3.5 Jack x 1
I/F Port	RS-232C	φ3.5 Jack x 1
	USB	USB B-type x 1
	Memory I/F	SD Slot x 1
Power Input		12V DC In x 1
GENERAL		
Operating Temperature		+5°C ~ +35°C
Operating Humidity		30% ~ 90%
Power		12V DC (Adaptor input : 100V AC ~ 240V free voltage, 50/60Hz, output : 12V, 4A)
Dimensions		In-use : 366(W) x 424(H) x 349(D)mm / ø14.41"(W) x 16.69"(H) x 13.74"(D)
Weight		3.5Kg (7.72 lb)
Accessories	Supplied	Remote controller, USB cable, DVI cable
	Accessories	VGA cable, Audio cable
	Optional	Microscope adaptor lens
	Accessories	RS-232C cable, SD card



The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.

Design and specifications are subject to change without notice.



SAMSUNG TECHWIN

SAMSUNG TECHWIN CO., LTD.

145-3, Sangdaewon 1-dong, Jungwon-gu, Seongnam-si, Gyeonggi-do Korea 462-703
Tel : +82-31-740-8160 Fax : +82-31-740-8145
www.samsungpresenter.com

SAMSUNG TECHWIN AMERICA Inc.
100 Challenger Road, #700 Ridgfield Park,
NJ 07660, UNITED STATES
Tel : +1-201-325-6920 Fax : +1-201-373-0124
www.samsungpresenterusa.com

SAMSUNG TECHWIN EUROPE CO., LTD.
Samsung House, 1000 Hillwood Drive, Hillwood Business Park
Chertsey, Surrey, UNITED KINGDOM KT16 0PS
Tel : +44-1932-45-5300 Fax : +44-1932-45-5325

■ DISTRIBUTED BY

